

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 :

C21D 9/56, F27B 9/24

A1

(11) International Publication Number:

WO 00/40766

(43) International Publication Date:

13 July 2000 (13.07.00)

(21) International Application Number: PCT/NL99/00822

(22) International Filing Date: 30 December 1999 (30.12.99)

(30) Priority Data:

1010971

6 January 1999 (06.01.99)

NL

(71) Applicant (for all designated States except US): THERMTEC B.V. [NL/NL]; Wijnhaven 76, NL-3011 WT Rotterdam (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): RUTTER, Leo, Antonius [NL/NL]; Rondweg 147, NL-2922 ET Krimpen Aan Den IJssel (NL).

(74) Agent: RIEMENS, R., H.; Exter Polak & Charlois B.V., P.O. Box 3241, NL-2280 GE Rijswijk (NL).


(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

In English translation (filed in Dutch).

(54) Title: STRIP GUIDING DEVICE COMPRISING A ROTATABLE CONSTRUCTION FOR CHANGING SUPPORTING ROLLS HAVING COOLING MEANS



(57) Abstract

Strip guiding device for guiding hot metal strip (20), comprising a frame (1), a support construction (3) which is accommodated in the frame (1) in such a manner that it can rotate about an axis (4), drive means (6) for the stepwise rotation of the support construction (3) in the frame (1), at least two supporting rolls (10, 11) which are rotatably and removably arranged in the support construction (3), insulating means which are connected to the support construction (3) and are positioned between the supporting rolls (10, 11), and cooling means for cooling each supporting roll (10, 11), in which device the cooling means for each supporting roll (10, 11) comprise a cooling body (25, 26) which is connected to the support construction (3), each cooling body (25, 26) extending in the longitudinal direction of the associated supporting roll (10, 11), externally delimiting this roll over part of the circumference, and being positioned at a distance from the support roll (10, 11), each cooling body (25, 26) cooling the associated supporting roll (10, 11) as a result of direct radiation from the said roll.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Short title: Strip guiding device comprising a rotatable construction for changing supporting rolls having cooling means

5 The invention relates to a strip guiding device of the type having a rotatable support construction with supporting rolls according to the preamble of claim 1.

 Strip guiding devices of this nature are known, inter alia from DE-C-3401792. This document describes a strip guiding
10 device which is intended to guide hot metal strip over supporting rolls between or inside horizontal furnace chambers of a continuous annealing furnace. In this case, the metal strip hangs freely between two or more strip guiding devices as it moves through the furnace chambers. Continuous annealing
15 furnaces are in widespread use, for example, for the oxidative annealing of stainless strip in a so-called annealing and pickling line. These furnaces operate at high temperatures and high production capacities. The strip guiding device in DE-C-34 01 792 comprises a support construction in roll form
20 which is rotatably accommodated in a frame. Two diametrically opposite, cylindrical cavities are formed in the roll-like support construction, in which cavities two supporting rolls are accommodated in a freely rotatable manner. The roll-like support construction substantially comprises a solid body with cooling
25 lines which extend inside it. The solid body provides insulation against the high temperatures in the furnace chamber for the supporting roll which is not in operation. Maintenance on the supporting roll which is at the top in operation can be carried out by rotating the support construction through 180°.

30 A drawback of the known strip guiding device is that the service life of the supporting rolls is limited by the insulating action. The temperature of the supporting roll which is in operation and over which the hot metal strip is guided rises considerably, which has an adverse effect on the service
35 life of the supporting roll. In addition, the high temperature increases so-called "pick-up" phenomena, i.e. the accumulation of small particles on the running surface of the supporting roll, leading to damage to the hot metal strip which is guided

over it. In order to reduce the temperature of the supporting roll, it is possible, inter alia, to arrange cooling means inside the supporting rolls. In the case of so-called fibre rolls, i.e. supporting rolls which are coated with fibre discs, however, the cooling action is limited owing to the insulating action of the fibre material. In practice, it has been found that indirect cooling of an operating supporting roll which is accommodated in a rotatable support construction by means of internal cooling lines does not sufficiently reduce the temperature of the running surface of this supporting roll. It is also known, in the case of metal supporting rolls with a metal outer casing, to guide cooling water directly along the inside of the outer metal casing. However, this results in very high heat losses from supporting rolls of this nature, and consequently the local cooling, particularly in the case of thin metal strip which is to be annealed, on the outer casing of the supporting roll is so high that it may lead to deformation of the metal strip.

The object of the invention is to overcome the abovementioned drawbacks, and, in particular, to provide a strip guiding device in which supporting rolls can be changed quickly, while at the same time a maximum possible service life of the supporting rolls at high furnace temperatures and high production capacities is also achieved. In particular, the object of the invention is to provide a strip guiding device in which good service lives can be achieved even for supporting rolls which are covered with fibre discs. Supporting rolls of this nature are preferably used for guiding thin, cold-rolled metal strip, which is highly susceptible to damage.

According to the invention, these objects are achieved by means of a strip guiding device according to claim 1. The strip guiding device comprises a support construction which is mounted in a frame and can be rotated in steps by means of drive means. At least two rotatable and exchangeable supporting rolls are arranged in the rotatable support construction. The supporting rolls are thermally insulated from one another by means of insulating means which are connected to the support construction. An external cooling body is provided for each

supporting roll. The cooling bodies are connected to the support construction, each cooling body externally surrounding the associated supporting roll over at least a quarter of its circumference. There is a small space between the cooling bodies and the supporting rolls. In operation, the top supporting roll, over which hot metal strip is guided, is cooled as a result of direct radiation to the cooling body. This allows the running surface of the supporting roll to be cooled in a very uniform but not excessively intensive manner. The resultant uniform, limited reduction in the temperature of the running surface significantly improves the service life of the supporting roll and considerably reduces pick-up, or even eliminates this phenomenon altogether. It has been found that with the strip guiding device according to the invention, fibre rolls can be used up to a few weeks even at very high temperatures, whereas in the devices used hitherto the supporting rolls often had to be replaced after only a few days. A further advantage is that a supporting roll which has been rotated out of its operating position can be cooled rapidly and uniformly, with the result that maintenance or replacement of the supporting roll can be carried out quickly. The efficient cooling of the running surface by means of direct radiation of heat from the roll advantageously allows a higher operating temperature of a furnace to be established without this leading to adverse "pick-up" phenomena or defects on the material of the supporting rolls. Furnace temperatures of up to approx. 1250°C are advantageously quite possible. In practice, it has been found that the temperature of the running surface of the operating supporting roll, via the cooling body which delimits more than 90° of the circumference of the supporting roll, is cooled sufficiently to allow the supporting roll to rotate at high speeds, thus allowing high production capacities.

It should be noted that FR-A-1,370,251 has disclosed a strip guiding device with bearing rolls which are accommodated in cavities in a solid thermally insulating body. Beneath each cavity, there is a cooling-liquid pipe for cooling the bearing roll via direct radiation of heat. However, this construction as such is relatively unsuitable for use in a strip guiding device

comprising a rotatable construction for changing supporting rolls. The removal of heat to the single, narrow cooling-liquid pipe in the bottom of the cavity is extremely limited, and consequently the circumferential speed of the supporting rolls has to be adapted in order to achieve a desired mean temperature for the supporting rolls. At furnace temperatures of over 1000°C, this mean supporting-roll temperature can only be sufficiently low to prevent sagging of the supporting rolls. The "pick-up" phenomenon and other damage to the surface structure of the supporting rolls will still be present. In particular, fibre rolls cannot be used in the construction described in FR-A-1,370,251, since even a temporary standstill of the supporting rolls would within a very short time damage these rolls to such an extent that they would have to be replaced.

The advantage of the construction according to the invention is that it can be used for all types of supporting rolls. For example, it can be used to guide hot-rolled metal strip with an oxide skin over metal supporting rolls provided with a bronze coating. In particular, so-called fibre rolls, in which, for example, metal supporting rolls are covered with fibre discs, can be successfully cooled on their running surface by means of the cooling construction according to the invention. In this way, it is possible for even thin, cold-rolled metal strip, which is highly susceptible to damage, to be guided successfully. It is noted that effective cooling of the running surface of fibre rolls with the heat being dissipated to a cooling body located inside the fibre roll is impossible, or only possible with great difficulty, owing to the very low coefficient of thermal conductivity of the fibre discs.

In particular, the cooling body delimits more than 140° of the circumference of the associated supporting roll. The extensive surrounding delimitation of the supporting roll by the cooling body ensures that there is sufficient cooling of the supporting roll even if the metal strip, and consequently the supporting roll, are temporarily at a standstill. This is advantageous since, in the known strip guiding devices, if the hot metal strip is at a standstill the support construction has to be rotated through an angle of 90°, in order to prevent

damage to the supporting roll as a result of overheating. In the case of the strip guiding device according to the invention, rotation of this nature is only necessary in the event of a defect to the cooling body or the cooling system.

5 Preferred embodiments of the invention are defined in claims 3-10.

The invention will be explained in more detail with reference to the appended drawing, in which:

Fig. 1 shows a view in longitudinal section of a strip
10 guiding device according to the invention;

Fig. 2 shows a view on an enlarged scale on line II-II in Fig. 1;

Fig. 3 shows a view of part of a cooling body from Fig. 2; and

15 Fig. 4 shows a view of part of an insulating means segment from Fig. 2.

The strip guiding device shown in Fig. 1 comprises a frame 1 with two upright legs. Each leg is provided with bearing means 2 in which a support construction 3 is accommodated in
20 such a manner that it can rotate about an axis 4. The vertical leg of the frame 1 which is located on the right-hand side comprises drive means 6 for the stepwise rotation of the support construction 3 in the frame 1. The support construction 3 has a top supporting roll 10 and a bottom supporting roll 11. The
25 supporting rolls 10, 11 are usually mounted in a freely rotatable manner in the support construction 3; however, they may also be driven.

The strip guiding device is intended to guide hot metal strip between or inside furnace chambers of a horizontal annealing furnace. In Fig. 2, the metal strip is
30 diagrammatically illustrated and is denoted by the reference numeral 20. In operation, the metal strip 20 is guided over the supporting roll 10. If necessary, maintenance can be carried out on the supporting roll 10 in a simple manner, by rotating the support construction 3 through an angle of 180°. In this way,
35 the supporting roll 10 moves to the bottom. While maintenance is being carried out on the supporting roll 10, the metal strip 20 is guided over the supporting roll 11.

The support construction 3 comprises a central pipe 14 on which cooling and insulating means are mounted. The cooling and insulating means are arranged between the supporting rolls 10 and 11 and extend over the entire length of the supporting rolls 10, 11.

The cooling means comprise an external cooling body 25, 26 for each supporting roll 10, 11 respectively (cf. Fig. 2). Each cooling body 25, 26 is located to the side of the associated supporting roll 10, 11, with a small gap left between the supporting roll 10, 11 and the cooling body 25, 26. The cooling body 25, 26 delimits a large part of the outer circumference of the supporting roll 10, 11, in particular almost half its external circumference. The cooling body 25 is permanently cooled, so that some of the heat from the supporting roll 10 which is in operation, which heat emanates from the hot metal strip and the furnace, can be dissipated to the cooling body 25 as a result of direct radiation of heat. The cooling body 26 is also permanently cooled. If the supporting roll 11 has just been rotated out of its operating position, its heat can be dissipated to the cooling body 26 as a result of direct radiation of heat. This allows maintenance work on the supporting roll 11 to be carried out rapidly.

Advantageously, the cooling body 25, 26 comprises a liquid-cooled body which is connected to a cooling-medium inlet 27 and a cooling-medium outlet 28 (cf. Fig. 1). The cooling medium, for example water or oil, enters one end of the pipe 14 via the cooling-medium inlet 27 and, from there, moves into the top and bottom cooling bodies 25, 26 via a manifold 29. After the cooling medium has flowed through the cooling bodies 25, 26, it is discharged via a manifold 30, an end of the pipe 14 and, from there, to the cooling-medium outlet 28. The central supply and discharge of cooling medium along the axis 4 is advantageous in particular during rotation of the support construction 3.

The cooling body 25, 26 may be designed in various ways, for example in the form of a plurality of pipes 32 which are positioned next to one another and are each connected to the cooling-medium inlet 27 and cooling-medium outlet 28. It is also possible to use one or more pipes which extend in meandering

form through the cooling body 25, 26. The advantage of this option is that just one connection to the cooling-medium inlet and outlet will be sufficient.

To insulate and protect the support construction 3, there are insulating shells 34 between the cooling bodies 25, 26. Stacked sets of insulating shells 34 are covered by heat-resistant plates 35. The sets of insulating shells 34 and heat-resistant plates 35 are held together with the aid of securing pins 36.

The cooling and insulating means between the supporting rolls 10, 11 are preferably of segmented structure and are separately attached to the pipe 14 of the support construction 3. This makes it possible to remove the separate segments without the entire support construction 3 having to be dismantled. The segmented structure can be clearly seen from Figs. 3 and 4. Both the cooling-means segment from Fig. 3 and the insulating-means segment from Fig. 4 are provided with a supporting rib 40 and 41, respectively, by means of which the segments can be fitted to one another and to the pipe 14. The insulating means are advantageously designed in such a manner that those edges of the cooling means which are located furthest outwards are protected from heat being radiated in directly from the furnace. This prevents excessive heat absorption.

The heat-resistant plates 35 substantially lie at a lesser radius from the centre axis 4 of the support construction 3 than the outermost parts of the supporting rolls 10, 11. During rotation of the support construction 3, the metal strip 20 can be supported on the heat-resistant plates 35 without damaging the insulation. In operation, part of the strip guiding device projects inwards through an opening in a bottom wall of a horizontal annealing furnace and/or adjoins a strip-feed or strip-removal opening in a side wall of the furnace. In order to allow rotation of the support construction, a gap is left clear between the edges of the opening in the furnace wall and the strip guiding device. In this case, it is advantageous for the heat-resistant plates 35 to be at a shorter radius from the centre axis 4 than the outermost parts of the supporting rolls 10, 11. Any contamination, for example burnt-on metal residues,

which builds up at the location of the edges of the opening is consequently free to fall downwards without becoming jammed between the plates 35 and the edges of the opening. During rotation of the support construction 3, the strip which is to be
5 guided is lowered a few centimetres until it is supported on the plates 35. To prevent the loss of flue gases from the furnace, partly as a result of the plates 35 being positioned at a shorter radius, air curtains are positioned along the entire length and at the ends of the support construction 3, which
10 curtains seal the furnace housing at the location of the gaps which have been left clear between the edges of the opening and the strip guiding device.

To prevent steam from flue gases in the annealing furnace condensing on surfaces of the cooling body 25 and other
15 water-cooled parts, the cooling medium is supplied at a specific initial temperature. This initial temperature is such that a temperature below the dewpoint on the surface of the cooling body 25 and other water-cooled parts is prevented. The initial temperature of the cooling medium is in particular in the
20 vicinity of 40-45°C.

In the case of thin strip, the supporting rolls 10, 11 are advantageously formed by so-called fibre rolls. In this case, each supporting roll substantially comprises a metal inner pipe 50 (cf. Fig. 2) over which a plurality of discs 51 have
25 been pushed, their outer edges together forming a running surface of the supporting roll. Each disc 51 is in this case made from fibrous material. The design of the strip guiding device according to the invention makes it possible to use fibre rolls of this nature, since the temperature of the running
30 surface of the fibre rolls can be kept within permissible limits as a result of the direct radiation of heat to the cooling body located beneath it.

Thus, the invention provides a strip guiding device with a rotatable support construction having two supporting rolls, in
35 which the service life of the supporting rolls is very long and a high operating temperature of an annealing furnace can be used without this leading to an excessive temperature of the supporting roll which is in operation.

CLAIMS

1. Strip guiding device for guiding hot metal strip (20), comprising:
 - 5 - a frame (1);
 - a support construction (3) which is accommodated in the frame (1) in such a manner that it can rotate about an axis (4);
 - drive means (6) for the stepwise rotation of the support construction (3) in the frame (1);
 - 10 - at least two supporting rolls (10, 11) which are rotatably and removably arranged in the support construction (3);
 - insulating means which are connected to the support construction (3) and are positioned between the supporting rolls (10, 11); and
 - 15 - cooling means for cooling each supporting roll (10, 11); characterized in that the cooling means for each supporting roll (10, 11) comprise a cooling body (25, 26) which is connected to the support construction (3), in which each cooling body (25, 20 26) extends in the longitudinal direction of the associated supporting roll (10, 11), externally delimits this roll over more than 90° of the circumference, and is positioned at a distance from the support roll (10, 11), each cooling body (25, 26) cooling the associated supporting roll (10, 11) as a result of direct radiation.
 - 25
2. Strip guiding device according to claim 1, in which the cooling body (25, 26) delimits more than 140° of the circumference of the associated supporting roll (10, 11).
- 30 3. Strip guiding device according to claim 1 or 2, in which the cooling body (25, 26) comprises a liquid-cooled body with a cooling-medium inlet (27) and a cooling-medium outlet (28).
- 35 4. Strip guiding device according to claim 3, in which the cooling body (25, 26) comprises at least one meandering pipe (21).

5. Strip guiding device according to one of the preceding claims, in which the insulating means comprises insulating shells (34) which extend between the cooling bodies (25, 26) of the separate supporting rolls (10, 11).

5

6. Strip guiding device according to claim 5, in which the insulating shells (34) are covered by a heat-resistant plating (35).

10

7. Strip guiding device according to claim 6, in which the heat-resistant plating (35) is located substantially at a shorter radius from the centre axis (4) of the support construction (3) than those parts of the supporting rolls (10, 11) which lie furthest outwards.

15

8. Strip guiding device according to one of the preceding claims, in which the insulating means are of segmented design and are attached to the support construction (3) in such a manner that they can be removed separately.

20

9. Strip guiding device according to one of the preceding claims, in which the cooling bodies (25, 26) are attached to the support construction (3) in such a manner that they can be removed separately.

25

10. Strip guiding device according to one of the preceding claims, in which the supporting roll (10, 11) comprises a core which is covered with fibre discs (51).

1/2




FIG. 1.




FIG. 2.




FIG. 3.




FIG. 4.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/NL 99/00822

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 C21D9/56 F27B9/24

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 C21D F27B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	FR 1 370 251 A (OFU OFENBAU-UNION) 14 December 1964 (1964-12-14) the whole document	1
Y	FR 2 540 138 A (OUTOKUMPU OY) 3 August 1984 (1984-08-03) cited in the application the whole document	1
A	EP 0 862 033 A (STEIN HEURTEY) 2 September 1998 (1998-09-02)	
A	US 4 049 372 A (BLOOM WILLIAM M) 20 September 1977 (1977-09-20)	
A	FR 2 344 800 A (ALLEGHENY LUDLUM IND INC) 14 October 1977 (1977-10-14)	
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *A* document member of the same patent family

Date of the actual completion of the international search

14 April 2000

Date of mailing of the international search report

26/04/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Mollet, G

INTERNATIONAL SEARCH REPORT

Inter. Application No
PCT/NL 99/00822

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 2 385 061 A (KOPPERS WISTRA OFENBAU GMBH) 20 October 1978 (1978-10-20)	
A	FR 2 660 935 A (SELAS SA) 18 October 1991 (1991-10-18)	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/NL 99/00822

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR 1370251 A	14-12-1964	DE 1303382 B	
FR 2540138 A	03-08-1984	FI 830284 A	28-07-1984
		AT 388941 B	25-09-1989
		AT 24684 A	15-02-1989
		BE 898688 A	16-05-1984
		BR 8400314 A	28-08-1984
		CA 1216420 A	13-01-1987
		DE 3401792 A	02-08-1984
		GB 2135033 A, B	22-08-1984
		IT 1195999 B	03-11-1988
		JP 1609021 C	28-06-1991
		JP 2033767 B	30-07-1990
		JP 59140326 A	11-08-1984
		KR 8904946 B	02-12-1989
		SE 461337 B	05-02-1990
		SE 8400103 A	28-07-1984
		US 4538986 A	03-09-1985
		ZA 8400222 A	26-09-1984
EP 0862033 A	02-09-1998	FR 2760077 A	28-08-1998
		DE 862033 T	06-05-1999
		ES 2119734 T	16-10-1998
		JP 10306323 A	17-11-1998
		US 5938431 A	17-08-1999
US 4049372 A	20-09-1977	NONE	
FR 2344800 A	14-10-1977	US 4069008 A	17-01-1978
		AT 358619 B	25-09-1980
		AT 836776 A	15-02-1980
		AU 497584 B	21-12-1978
		AU 1887376 A	27-04-1978
		BE 849762 A	22-06-1977
		BR 7607857 A	25-10-1977
		CA 1073787 A	18-03-1980
		DE 2650998 A	29-09-1977
		ES 452874 A	16-12-1977
		GB 1524140 A	06-09-1978
		IN 146822 A	22-09-1979
		IN 147500 A	15-03-1980
		IT 1074953 B	22-04-1985
		JP 1267856 C	10-06-1985
		JP 52114408 A	26-09-1977
		JP 59042057 B	12-10-1984
		LU 76444 A	18-01-1978
		NL 7612903 A	21-09-1977
		RO 73597 A	04-11-1981
		SE 434779 B	13-08-1984
		SE 7611502 A	20-09-1977
		YU 73277 A	31-10-1982
		ZA 7606189 A	28-09-1977
FR 2385061 A	20-10-1978	DE 2713139 A	05-10-1978
		JP 53134251 A	22-11-1978
		US 4182611 A	08-01-1980
FR 2660935 A	18-10-1991	NONE	

Form PCT/ISA/210 (patent family annex) (July 1992)